1.00/1.001

Introduction to Computers and Engineering Problem Solving Quiz 2 / Fall 2008

Name:	
Email Address:	
TA:	
Section:	

You have 80 minutes to complete this quiz. For coding questions, you do not need to include comments, and you should assume that all necessary files have already been imported.

Good luck!

Question	Points
Question 1	/30
Question 2	/20
Question 3	/30
Question 4	/20
Total	/100

Question 1. ArrayLists (30 points)

You are the director of a large cruise ship. There are two classes in your program: Passenger and CruiseShip. The Passenger class, which represents a single passenger on the ship, has three data members: the passenger's age, name, and a boolean variable stating whether the passenger is a first class passenger or not. Passenger is defined as follows:

```
package travel;
public class Passenger
{
    String name;
    int age;
    boolean isFirstClass;
    //isFirstClass is true when the passenger is a first class
    //passenger, false otherwise

public Passenger(String n, int a, boolean c) {
        name = n;
        age = a;
        isFirstClass = c;
    }
}
```

The CruiseShip class contains an ArrayList of Passengers, a constructor, and two additional methods.

//code continued on next page

Complete the missing code for the methods as described in the comments above each.

```
package travel;
public class CruiseShip
     ArrayList<Passenger> passengers;
      * The constructor simply initializes passengers
      * to an empty ArrayList.
     public CruiseShip() {
      * This method adds the inputted Passenger p
      * to the ArrayList passengers.
     public void addPassenger(Passenger p) {
```

//code continued on next page

```
/*
     * This method returns an ArrayList of Passengers that meet the
      * criteria to have access to the cruise ship's exclusive club.
      ^{\star} These passengers must have first class status, and must have an
      * age of at least 21
      */
     public ArrayList<Passenger> getExclusiveMembers() {
}
```

Question 2. Multiple Choice (20 points)

Circle all answers that are correct.

1. You always have to add a "throws" clause to a method signature if the method could throw an exception.

TRUE FALSE

2. Consider the following code:

```
public class EnclosingClass {
   int counter;
   private static class MysteryClass {
      public MysteryClass() {
         counter++;
      }
   }
}
```

a. Is MysteryClass an inner class or nested class

Inner Class Nested Class

b. This code will compile.

TRUE FALSE

3. A concrete class that extends an abstract class must implement all abstract methods.

TRUE FALSE

4. A class can extend multiple classes.

TRUE FALSE

5. A subclass can access _____ fields of its superclass in the same package.

Public Protected Private Package No

6. An abstract class may have

Public fields Protected fields Private fields

Question 3. Swing (30 points)

Read the following program then answer the questions which involve drawing the JFrame QuirkyCalculator initially and after buttons are pressed. Assume all necessary classes have been imported.

```
public class QuirkyCalculator extends JFrame implements
ActionListener{
    JPanel panel1 = new JPanel();
    JLabel totalLabel = new JLabel("total: 0");
    JPanel panel2 = new JPanel();
    JPanel panel3 = new JPanel();
    int total=0;
    JButton a = new JButton("Button A");
    JButton b = new JButton("Button B");
    JButton c = new JButton("Button C");
   public QuirkyCalculator (String name) {
        super(name);
    }
    public void addComponentsToPane(final Container pane) {
        a.addActionListener(this);
        b.addActionListener(this);
        c.addActionListener(this);
        panel1.add(new JLabel("Pick one"));
        panel2.add(a);
        panel2.add(b);
        panel2.add(c);
        panel3.add(totalLabel);
        pane.add(panel2, BorderLayout.CENTER);
        pane.add(panel1, BorderLayout.NORTH);
        pane.add(panel3, BorderLayout.SOUTH);
    }
//code continues on next page
```

```
public void actionPerformed(ActionEvent e) {
       if(e.getSource().equals(a)){
           total+=1;
       if(e.getSource().equals(b)){
           total*=2;
           totalLabel.setText("total: "+total);
       if(e.getSource().equals(c)){
           total-=1;
           totalLabel.setText("total: "+total);
       }
   }
  public static void main(String[] args) {
       QuirkyCalculator frame = new QuirkyCalculator ("Quirky");
       frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
       frame.addComponentsToPane(frame.getContentPane());
       frame.pack();
    }
```

The user	has clicke	ed on Butt	on C ther	n Button B	then Butto	n A. Draw	the JFra	me a
	ars. Be a	ccurate a	bout labels	s and layou				
now appe	ars. Be a	ccurate a	bout labels	s and layou				
now appe	ars. Be a	ccurate a	bout labels	s and layou				
now appe	ars. Be a	ccurate a	bout labels	s and layou				
now appe	ars. Be a	ccurate a	bout labels	s and layou				
now appe	ars. Be a	ccurate a	bout labels	s and layou				
now appe	ars. Be a	ccurate a	bout labels	s and layou				

Question 4: Recursion (20 points)

Read the following methods and write <u>either</u> the expression implemented by the method (e.g., $\frac{x}{y}$ or $\sqrt[x]{y}$) <u>or</u> the numerical value returned by the method call. Either will be counted as correct.

Assume that x and y are positive. Show work for partial credit.

```
1. public static int methodA(int x, int y) {
        if(y == 1) {
            return x;
        }
        else{
            return x + methodA(x, y - 1);
        }
}
```

```
2. public static int methodB(int x, int y) {
    if(x < y) {
        return x;
    }
    else{
        return methodB(x-y, y);
    }
}</pre>
```

1.00 / 1.001 / 1.002 Introduction to Computers and Engineering Problem Solving Spring 2012

For information about citing these materials or our Terms of Use, visit: http://ocw.mit.edu/terms.