III.H Zeroth Order Hydrodynamics

As a first approximation, we shall assume that in *local equilibrium*, the density f_1 at each point in space can be represented as in eq.(III.56), i.e.

$$f_1^0(\vec{p}, \vec{q}, t) = \frac{n(\vec{q}, t)}{\left(2\pi m k_B T(\vec{q}, t)\right)^{3/2}} \exp\left[-\frac{\left(\vec{p} - m \vec{u}(\vec{q}, t)\right)^2}{2m k_B T(\vec{q}, t)}\right].$$
 (III.93)

The choice of parameters clearly enforces $\int d^3 \vec{p} f_1^0 = n$, and $\langle \vec{p}/m \rangle^0 = \vec{u}$, as required. Average values are easily calculated from this Gaussian weight; in particular

$$\langle c_{\alpha}c_{\beta}\rangle^{0} = \frac{k_{B}T}{m}\delta_{\alpha\beta},$$
 (III.94)

leading to

$$P^{0}_{\alpha\beta} = nk_B T \delta_{\alpha\beta}, \quad \text{and} \quad \varepsilon = \frac{3}{2} k_B T.$$
 (III.95)

Since the density f_1^0 is even in \vec{c} , all odd expectation values vanish, and in particular

$$\vec{h}^0 = 0. \tag{III.96}$$

The conservation laws in this approximation take the simple forms

$$\begin{cases} D_t n = -n\partial_{\alpha}u_{\alpha} \\ mD_t u_{\alpha} = F_{\alpha} - \frac{1}{n}\partial_{\alpha} (nk_B T) \\ D_t T = -\frac{2}{3}T\partial_{\alpha}u_{\alpha} \end{cases}$$
(III.97)

In the above expression, we have introduced the material derivative

$$D_t \equiv \left[\partial_t + u_\beta \partial_\beta\right],\tag{III.98}$$

which measures the time variations of any quantity as it moves along the stream-lines set up by the average velocity field \vec{u} . By combining the first and third equations, it is easy to get

$$D_t \ln\left(nT^{-3/2}\right) = 0. \tag{III.99}$$

The quantity $\ln(nT^{-3/2})$ is like a local entropy for the gas (see eq.(III.67)), which according to the above equation is not changed along stream-lines. The zeroth order hydrodynamics thus predicts that the gas flow is adiabatic. This prevents the local equilibrium solution of eq.(III.93) from reaching a true global equilibrium form which necessitates an increase in entropy.

To demonstrate that eqs.(III.97) do not describe a satisfactory approach to equilibrium, examine the evolution of small deformations about a stationary ($\vec{u}_0 = 0$) state, in a uniform box ($\vec{F} = 0$), by setting

$$\begin{cases} n(\vec{q},t) = \overline{n} + \nu(\vec{q},t) \\ T(\vec{q},t) = \overline{T} + \theta(\vec{q},t) \end{cases}$$
 (III.100)

We shall next expand eqs.(III.97) to first order in the deviations (ν, θ, \vec{u}) . Note that to lowest order, $D_t = \partial_t + O(u)$, leading to the linearized zeroth order hydrodynamic equations

$$\begin{cases} \partial_t \nu = -\overline{n} \partial_\alpha u_\alpha \\ m \partial_t u_\alpha = -\frac{k_B \overline{T}}{\overline{n}} \partial_\alpha \nu - k_B \partial_\alpha \theta \\ \partial_t \theta = -\frac{2}{3} \overline{T} \partial_\alpha u_\alpha \end{cases}$$
(III.101)

• Normal modes of the system are obtained by Fourier transformations,

$$A\left(\vec{k},\omega\right) = \int d^{3}\vec{q}\,dt\,\exp\left[i\left(\vec{k}\cdot\vec{q}-\omega t\right)\right]A\left(\vec{q},t\right),\tag{III.102}$$

where A stands for any of the three fields (ν, θ, \vec{u}) . The natural vibration frequencies are solutions to the matrix equation

$$\omega \begin{pmatrix} \nu \\ u_{\alpha} \\ \theta \end{pmatrix} = \begin{pmatrix} 0 & \overline{n}k_{\beta} & 0 \\ \frac{k_{B}\overline{T}}{m\overline{n}}\delta_{\alpha\beta}k_{\beta} & 0 & \frac{k_{B}}{m}\delta_{\alpha\beta}k_{\beta} \\ 0 & \frac{2}{3}\overline{T}k_{\beta} & 0 \end{pmatrix} \begin{pmatrix} \nu \\ u_{\beta} \\ \theta \end{pmatrix}.$$
 (III.103)

It is easy to check that this equation has the following modes, the first *three* with zero frequency:

- (a) Two modes describe shear flows in a uniform $(n = \overline{n})$ and isothermal $(T = \overline{T})$ fluid, in which the velocity varies along a direction normal to its orientation (e.g. $\vec{u} = f(x, t)\hat{y}$). In terms of Fourier modes $\vec{k} \cdot \vec{u}_T(\vec{k}) = 0$, indicating *transverse* flows that are not relaxed in this zeroth order approximation.
- (b) A third zero frequency mode describes a stationary fluid with uniform pressure $P = nk_BT$. While n and T may vary across space, their product is constant, insuring

that the fluid will not start moving due to pressure variations. The corresponding eigenvector of eq.(III.103) is

$$\mathbf{v}_{\mathbf{e}} = \begin{pmatrix} \overline{n} \\ 0 \\ -\overline{T} \end{pmatrix}.$$
 (III.104)

(c) Finally, the *longitudinal* velocity $(\vec{u}_{\ell} \parallel \vec{k})$ combines with density and temperature variations in eigenmodes of the form

$$\mathbf{v}_{\mathbf{l}} = \begin{pmatrix} \overline{n} |\vec{k}| \\ \omega(\vec{k}) \\ \frac{2}{3}\overline{T} |\vec{k}| \end{pmatrix}, \quad \text{with} \quad \omega(\vec{k}) = \pm v_{\ell} |\vec{k}|, \quad (\text{III.105})$$

where

$$v_{\ell} = \sqrt{\frac{5}{3} \frac{k_B \overline{T}}{m}},\tag{III.106}$$

is the longitudinal sound velocity. Note that the density and temperature variations in this mode are *adiabatic*, i.e. the local entropy (proportional to $\ln(nT^{-3/2})$) is left unchanged.

We thus find that none of the conserved quantities relaxes to equilibrium in the zeroth order approximation. Shear flow and entropy modes persist forever, while the two sound modes have undamped oscillations. This is a deficiency of the zeroth order approximation which is removed by finding a better solution to the Boltzmann equation.

III.I First Order Hydrodynamics

While $f_1^0(\vec{p}, \vec{q}, t)$ of eq.(III.93) does set the right hand side of the Boltzmann equation to zero, it is not a full solution, as the left hand side causes its form to vary. The left hand side is a *linear* differential operator, which using the various notations introduced in the previous sections, can be written as

$$\mathcal{L}[f] \equiv \left[\partial_t + \frac{p_\alpha}{m}\partial_\alpha + F_\alpha \frac{\partial}{\partial p_\alpha}\right] f = \left[D_t + c_\alpha \partial_\alpha + \frac{F_\alpha}{m} \frac{\partial}{\partial c_\alpha}\right] f.$$
(III.107)

It is simpler to examine the effect of \mathcal{L} on $\ln f_1^0$. which can be written as

$$\ln f_1^0 = \ln \left(nT^{-3/2} \right) - \frac{mc^2}{2k_B T} - \frac{3}{2} \ln \left(2\pi m k_B \right).$$
(III.108)

Using the relation $\partial(c^2/2) = c_\beta \partial c_\beta = -c_\beta \partial u_\beta$, we get

$$\mathcal{L}\left[\ln f_{1}^{0}\right] = D_{t}\ln\left(nT^{-3/2}\right) + \frac{mc^{2}}{2k_{B}T^{2}}D_{t}T + \frac{m}{k_{B}T}c_{\alpha}D_{t}u_{\alpha} + c_{\alpha}\left(\frac{\partial_{\alpha}n}{n} - \frac{3}{2}\frac{\partial_{\alpha}T}{T}\right) + \frac{mc^{2}}{2k_{B}T^{2}}c_{\alpha}\partial_{\alpha}T + \frac{m}{k_{B}T}c_{\alpha}c_{\beta}\partial_{\alpha}u_{\beta} - \frac{F_{\alpha}c_{\alpha}}{k_{B}T}.$$
(III.109)

If the fields n, T, and u_{α} , satisfy the zeroth order hydrodynamic eqs.(III.97), we can simplify the above equation to

$$\mathcal{L}\left[\ln f_{1}^{0}\right] = 0 - \frac{mc^{2}}{3k_{B}T}\partial_{\alpha}u_{\alpha} + c_{\alpha}\left[\left(\frac{F_{\alpha}}{k_{B}T} - \frac{\partial_{\alpha}n}{n} - \frac{\partial_{\alpha}T}{T}\right) + \left(\frac{\partial_{\alpha}n}{n} - \frac{3}{2}\frac{\partial_{\alpha}T}{T}\right) - \frac{F_{\alpha}}{k_{B}T}\right] \\ + \frac{mc^{2}}{2k_{B}T^{2}}c_{\alpha}\partial_{\alpha}T + \frac{m}{k_{B}T}c_{\alpha}c_{\beta}u_{\alpha\beta} \\ = \frac{m}{k_{B}T}\left(c_{\alpha}c_{\beta} - \frac{\delta_{\alpha\beta}}{3}c^{2}\right)u_{\alpha\beta} + \left(\frac{mc^{2}}{2k_{B}T} - \frac{5}{2}\right)\frac{c_{\alpha}}{T}\partial_{\alpha}T.$$
(III.110)

The characteristic time scale τ_U for \mathcal{L} is *extrinsic*, and can be made much larger than τ_{\times} . The zeroth order result is thus exact in the limit $(\tau_{\times}/\tau_U) \to 0$; and corrections can be constructed in a perturbation series in (τ_{\times}/τ_U) . To this purpose, we set $f_1 = f_1^0(1+g)$, and linearize the collision operator as

$$C[f_1, f_1] = -\int d^3 \vec{p}_2 d^2 \vec{b} \, |\vec{v}_1 - \vec{v}_2| f_1^0(\vec{p}_1) f_1^0(\vec{p}_2) \, [g(\vec{p}_1) + g(\vec{p}_2) - g(\vec{p}_1') - g(\vec{p}_2')]$$

$$\equiv -f_1^0(\vec{p}_1) C_L[g].$$
(III.111)

While linear, the above integral operator is still difficult to manipulate in general. As a first approximation, and noting its characteristic magnitude, we set

$$C_L[g] \approx \frac{g}{\tau_{\times}}.$$
 (III.112)

This is known as the single collision time approximation, and from the linearized Boltzmann equation $\mathcal{L}[f_1] = -f_1^0 C_L[g]$, we obtain

$$g = -\tau_{\times} \frac{1}{f_1^0} \mathcal{L}\left[f_1\right] \approx -\tau_{\times} \mathcal{L}\left[\ln f_1^0\right], \qquad (\text{III.113})$$

where we have kept only the leading term. Thus the first order solution is given by (using eq.(III.110))

$$f_{1}^{1}(\vec{p},\vec{q},t) = f_{1}^{0}(\vec{p},\vec{q},t) \left[1 - \frac{\tau_{\mu}m}{k_{B}T} \left(c_{\alpha}c_{\beta} - \frac{\delta_{\alpha\beta}}{3}c^{2} \right) u_{\alpha\beta} - \tau_{K} \left(\frac{mc^{2}}{2k_{B}T} - \frac{5}{2} \right) \frac{c_{\alpha}}{T} \partial_{\alpha}T \right],$$
(III.114)

where $\tau_{\mu} = \tau_{K} = \tau_{\times}$ in the single collision time approximation. However, in writing the above equation, we have anticipated the possibility of $\tau_{\mu} \neq \tau_{K}$ which arises in more sophisticated treatments (although both times are still of order of τ_{\times}).

It is easy to check that $\int d^3 \vec{p} f_1^1 = \int d^3 \vec{p} f_1^0 = n$, and thus various local expectation values are calculated to first order as

$$\langle \mathcal{O} \rangle^1 = \frac{1}{n} \int d^3 \vec{p} \, \mathcal{O} f_1^0(1+g) = \langle \mathcal{O} \rangle^0 + \langle g \mathcal{O} \rangle^0.$$
 (III.115)

The calculation of averages over products of c_{α} 's, distributed according to the Gaussian weight of f_1^0 , is greatly simplified by the use of *Wick's theorem*, which states that expectation value of the product is the sum over all possible products of paired expectation values, for example

$$\left\langle c_{\alpha}c_{\beta}c_{\gamma}c_{\delta}\right\rangle_{0} = \left(\frac{k_{B}T}{m}\right)^{2} \left(\delta_{\alpha\beta}\delta_{\gamma\delta} + \delta_{\alpha\gamma}\delta_{\beta\delta} + \delta_{\alpha\delta}\delta_{\beta\gamma}\right).$$
(III.116)

(Expectation values involving a product of an odd number of c_{α} 's are zero by symmetry.) Using this result, it is easy to verify that

$$\left\langle \frac{p_{\alpha}}{m} \right\rangle^{1} = u_{\alpha} - \tau_{K} \frac{\partial_{\beta} T}{T} \left\langle \left(\frac{mc^{2}}{2k_{B}T} - \frac{5}{2} \right) c_{\alpha} c_{\beta} \right\rangle^{0} = u_{\alpha}.$$
(III.117)

The pressure tensor at first order is given by

$$P_{\alpha\beta}^{1} = nm \left\langle c_{\alpha}c_{\beta}\right\rangle^{1} = nm \left[\left\langle c_{\alpha}c_{\beta}\right\rangle^{0} - \frac{\tau_{\mu}m}{k_{B}T} \left\langle c_{\alpha}c_{\beta}\left(c_{\mu}c_{\nu} - \frac{\delta_{\mu\nu}}{3}c^{2}\right) \right\rangle^{0} u_{\mu\nu} \right]$$

$$= nk_{B}T\delta_{\alpha\beta} - 2nk_{B}T\tau_{\mu}\left(u_{\alpha\beta} - \frac{\delta_{\alpha\beta}}{3}u_{\gamma\gamma}\right).$$
 (III.118)

(Using the above result, we can further verify that $\varepsilon^1 = \langle mc^2/2 \rangle^1 = 3k_BT/2$, as before.) Finally, the heat flux is given by

$$h_{\alpha}^{1} = n \left\langle c_{\alpha} \frac{mc^{2}}{2} \right\rangle^{1} = -\frac{nm\tau_{K}}{2} \frac{\partial_{\beta}T}{T} \left\langle \left(\frac{mc^{2}}{2k_{B}T} - \frac{5}{2} \right) c_{\alpha}c_{\beta}c^{2} \right\rangle^{0}$$

$$= -\frac{5}{2} \frac{nk_{B}^{2}T\tau_{K}}{m} \partial_{\alpha}T.$$
(III.119)

At this order, we find that spatial variations in temperature generate a heat flow that tends to smooth them out, while shear flows are opposed by the off-diagonal terms in the pressure tensor. These effects are sufficient to cause relaxation to equilibrium, as can be seen by examining the modified behavior of the modes discussed previously. (a) The pressure tensor now has an off-diagonal term

$$P^{1}_{\alpha\neq\beta} = -2nk_{B}T\tau_{\mu}u_{\alpha\beta} \equiv -\mu\left(\partial_{\alpha}u_{\beta} + \partial_{\beta}u_{\alpha}\right), \qquad (\text{III.120})$$

where $\mu \equiv nk_B T \tau_{\mu}$ is the viscosity coefficient. A shearing of the fluid (e.g. described by a velocity $u_y(x,t)$) now leads to a viscous force that opposes it (proportional to $\mu \partial_x^2 u_y$), causing its diffusive relaxation as discussed below.

(b) Similarly, a temperature gradient leads to a heat flux

$$\vec{h} = -K\nabla T, \tag{III.121}$$

where $K = (5nk_B^2 T \tau_K)/(2m)$ is the coefficient of thermal conductivity of the gas. If the gas is at rest ($\vec{u} = 0$, and uniform $P = nk_B T$), variations in temperature now satisfy

$$n\partial_t \varepsilon = \frac{3}{2} n k_B \partial_t T = -\partial_\alpha \left(-K \partial_\alpha T \right), \quad \Rightarrow \quad \partial_t T = \frac{2K}{3nk_B} \nabla^2 T.$$
(III.122)

This is the Fourier equation and shows that temperature variations relax by diffusion.

We can discuss the behavior of all the modes by linearizing the equations of motion. The first order contribution to $D_t u_{\alpha} \approx \partial_t u_{\alpha}$ is

$$\delta^{1}\left(\partial_{t}u_{\alpha}\right) \equiv \frac{1}{mn}\partial_{\beta}\delta^{1}P_{\alpha\beta} \approx -\frac{\mu}{m\overline{n}}\left(\frac{1}{3}\partial_{\alpha}\partial_{\beta} + \delta_{\alpha\beta}\partial_{\gamma}\partial_{\gamma}\right)u_{\beta},\tag{III.123}$$

where $\mu \equiv \overline{n}k_B\overline{T}\tau_{\mu}$. Similarly, the correction for $D_tT \approx \partial_t\theta$, is given by

$$\delta^{1}(\partial_{t}\theta) \equiv -\frac{2}{3k_{B}n}\partial_{\alpha}h_{\alpha} \approx -\frac{2K}{3k_{B}\overline{n}}\partial_{\alpha}\partial_{\alpha}\theta, \qquad (\text{III.124})$$

with $K = (5\overline{n}k_B^2\overline{T}\tau_K)/(2m)$. After Fourier transformation, the matrix equation (III.103) is modified to

$$\omega \begin{pmatrix} \nu \\ u_{\alpha} \\ \theta \end{pmatrix} = \begin{pmatrix} 0 & \overline{n}\delta_{\alpha\beta}k_{\beta} & 0 \\ \frac{k_{B}\overline{T}}{m\overline{n}}\delta_{\alpha\beta}k_{\beta} & -i\frac{\mu}{m\overline{n}}\left(k^{2}\delta_{\alpha\beta} + \frac{k_{\alpha}k_{\beta}}{3}\right) & \frac{k_{B}}{m}\delta_{\alpha\beta}k_{\beta} \\ 0 & \frac{2}{3}\overline{T}\delta_{\alpha\beta}k_{\beta} & -i\frac{2Kk^{2}}{3k_{B}\overline{n}} \end{pmatrix} \begin{pmatrix} \nu \\ u_{\beta} \\ \theta \end{pmatrix}.$$
(III.125)

We can ask how the normal mode frequencies calculated in the zeroth order approximation are modified at this order. It is simple to verify that the transverse (shear) normal models $(\vec{k} \cdot \vec{u}_T = 0)$ now have a frequency

$$\omega_T = -i\frac{\mu}{m\overline{n}}k^2. \tag{III.126}$$

The imaginary frequency implies that these modes are damped over a characteristic time $\tau_T(k) \sim 1/|\omega_T| \sim (\lambda)^2/(\tau_{\mu}\overline{v}^2)$, where λ is the corresponding wavelength, and $\overline{v} \sim \sqrt{k_B T/m}$ is a typical gas particle velocity. We see that the characteristic time scales grow as the square of the wavelength, which is characteristic of *diffusive* processes.

In the remaining normal modes the velocity is parallel to \vec{k} , and eq.(III.125) reduces to

$$\omega \begin{pmatrix} \nu \\ u_{\ell} \\ \theta \end{pmatrix} = \begin{pmatrix} 0 & \overline{n}k & 0 \\ \frac{k_B \overline{T}}{m\overline{n}}k & -i\frac{4\mu k^2}{3m\overline{n}} & \frac{k_B}{m}k \\ 0 & \frac{2}{3}\overline{T}k & -i\frac{2Kk^2}{3k_B\overline{n}} \end{pmatrix} \begin{pmatrix} \nu \\ u_{\beta} \\ \theta \end{pmatrix}.$$
 (III.127)

The determinant of the dynamical matrix is the product of the three eigen-frequencies, and to lowest order is given by

$$\det(M) = i \frac{2Kk^2}{3k_B\overline{n}} \cdot \overline{n}k \cdot \frac{k_B\overline{T}k}{m\overline{n}} + \mathcal{O}(\tau_{\times}^2).$$
(III.128)

At zeroth order the two sound modes have $\omega_{\pm}^{0}(k) = \pm v_{\ell}k$, and hence the frequency of the isobaric mode is

$$\omega_e^1(k) \approx \frac{\det(M)}{-v_\ell^2 k^2} = -i \frac{2Kk^2}{5k_B \overline{n}} + \mathcal{O}(\tau_{\chi}^2).$$
(III.129)

At first order, the longitudinal sound modes also turn into damped oscillations with frequencies $\omega_{\pm}^1(k) = \pm v_{\ell}k - i\gamma$. The simplest way to obtain the decay rates is to note that the trace of the dynamical matrix is equal to the sum of the eigenvalues, and hence

$$\omega_{\pm}^{1}(k) = \pm v_{\ell}k - ik^{2} \left(\frac{2\mu}{3m\overline{n}} + \frac{2K}{15k_{B}\overline{n}}\right) + \mathcal{O}(\tau_{\times}^{2}).$$
(III.130)

The damping of all normal modes guarantees the, albeit slow, approach of the gas to its final uniform and stationary equilibrium state.

8.333 Statistical Mechanics I: Statistical Mechanics of Particles Fall 2013

For information about citing these materials or our Terms of Use, visit: http://ocw.mit.edu/terms.